

主要数据 Main technical data:

认证 Certification | 防爆标志 Ex mark | 符合标准 Meet the standard

China (PCEC Ex)	Ex e II C Gb DIP A21	GB3836 GB12476
IECEX	Ex e II C Gb Ex tb III C Db	IEC60079
ATEX	Ex II 2 GD Ex e II C Gb Ex tb III C Db	EN60079

适用范围: 用于 1 区和 2 区

Intended use: Can be used in zone 1 and zone 2

用于 21 区和 22 区

Can be used in zone 21 and zone 22

 使用环境温度: $-40^{\circ}\text{C} < \text{Ta} < 80^{\circ}\text{C}$

 Ambient temperature: $-40^{\circ}\text{C} < \text{Ta} < 80^{\circ}\text{C}$

防护等级: IP66

Degree of protection: IP66

材 料: 铜制表面镀镍

Material: nickel plated brass

订购规格 Order specifications:

 CZ0227 金属电缆密封套
 CZ0227 Metal cable glands

图样 Illustration	编码 Code	入口螺纹 Entry thread	电缆直径 Cable diameter	G	L _{max}	L1	L2	SW	订购号 Order No.
	L02	M25 × 1.5	Φ11-15	G3/4"	52	15	24	32	CZ0227 2515 e202
	L03	M32 × 1.5	Φ11-19	G1"	55	15	25	38	CZ0227 3215 e203

订购规格 Order specifications:

 CZ0221 金属电缆密封套
 CZ0221 Metal cable glands

图样 Illustration	编码 Code	入口螺纹 Entry thread	电缆直径 Cable diameter	SW	螺纹长度 L1 Length of thread L1	长度 L2 Length L2	订购号 Order No.
	C03	M25 × 1.5	Φ8-17	32	15	33	CZ0221 2515 e403
	C04	M32 × 1.5	Φ12-21	37	16	39	CZ0221 3216 e404

订购规格 Order specifications:

 CZ0226 增安型电缆密封套 (填料函)
 CZ0226 Increased safety cable glands (stopping boxes)

图样 Illustration	编码 Code	入口螺纹 Entry thread	电缆直径 Cable diameter		L	L1	SW	钢带厚度 C Armour wire thickness C	订购号 Order No.
			A	B					
	G02	M25 × 1.5	6-12.5	11.5-16	76	15	32	0.85	CZ0226 2515 e002
	G03	M25 × 1.5	6.5-12.5	15-21	76	15	37	0.9	CZ0226 2515 e003
	G04	M32 × 1.5	11-18.5	20.5-27.5	85	15	44	1.25	CZ0226 3215 e004