



- 描述:**
- 钢模压铸成型
  - 表面喷涂纯环氧树脂
  - 内装欧司朗镇流器、触发器、电容器
  - 钢管布线、电缆布线

**Descriptions:**

- Die-casting aluminum alloy
- Surface is sprayed with pure epoxy resin.
- The ballast, trigger, capacitor of OSRAM brand are built-in.
- Pipe wiring or cable wiring.

**1 区和 2 区**  
**21 区和 22 区**  
**Zone 1 and zone 2**  
**Zone 21 and zone 22**

● **主要数据 Main technical data:**

认证 Certification | 防爆标志 Ex mark | 符合标准 Meet the standard

China (CQST Ex) Ex d IIC T5/T6 DIP A21 TA, T5/T6 GB3836 GB12476

适用范围: 用于 1 区和 2 区; 用于 21 区和 22 区

防护等级: IP66

使用环境温度:  $-40^{\circ}\text{C} < \text{Ta} < 50^{\circ}\text{C}$  ( $40^{\circ}\text{C}$ )

额定电压: 220V 50Hz

电缆入口:  $3 \times \text{G}3/4"$ , 电缆外径:  $\Phi 8-11.5\text{mm}$

Intended use: Can be used in zone 1 and zone 2

Can be used in zone 21 and zone 22

Degree of protection: IP66

Ambient temperature:  $-40^{\circ}\text{C} < \text{Ta} < 50^{\circ}\text{C}$  ( $40^{\circ}\text{C}$ )

Rated voltage: 220V 50Hz

Cable entry:  $3 \times \text{G}3/4"$ , Cable outside diameter:  $\Phi 8-11.5\text{mm}$

● **订购规格 Order specifications:**

图样 Illustration	名称 Light source code	功率 Power	温度组别T* Temperature class*		订购号 Code No.
			Ta≤40℃	Ta≤50℃	
	金属卤化物灯镇流器 Ballast of metal halide lamp	J70W	T6	T6	<b>CZ085A-J70W</b>
		J100W	T6	T6	<b>CZ085A-J100W</b>
		J150W	T6	T6	<b>CZ085A-J150W</b>
		J250W	T6	T5	<b>CZ085A-J250W</b>
		J400W	T6	T5	<b>CZ085A-J400W</b>
	高压钠灯镇流器	N70W	T6	T6	<b>CZ085A-N70W</b>
		N150W	T6	T6	<b>CZ085A-N150W</b>