



### 描述

三防泛光灯外壳由铝合金压铸成型，表面喷涂纯环氧树脂粉末，抗腐蚀性能好。透明罩采用硼硅酸盐钢化玻璃，外露紧固件采用不锈钢材料。内装高纯铝镜面反射器，照明范围大、亮度高。三防灯的接线盒从下面进线，适用于橡胶套和铠装电缆布线，内部接线端子选用笼式端子，便于接线。三防泛光灯内装金属卤化物灯、高压钠灯、电磁感应节能灯及镇流器、触发器等电器。能满足石油、化工、医药、军工、食品、电厂等企业的照明之用。

- 防护等级高达IP66
- 金属卤化物灯和高压钠灯灯泡设有防震保护，可从侧面更换灯泡，操作方便。
- 安装支架设有刻度盘
- 安装维护方便

### Descriptions:


The enclosures of weather-proof floodlight light fittings are made of die-cast aluminum alloy, with epoxy resin powder sprayed on their surfaces, so that they have good anti-corrosion performance. The transparent shield is made by the toughened glass of borosilicate, and the exposed fasteners are made of stainless steel. The high-purity aluminum reflector with broad illuminated area and high-brightness is mounted in. Weather-proof, floodlight light fitting's terminal box down entry, is suitable for rubber-coated and the armored cable wiring. The cage type terminals are selected as the internal terminals, which are convenient for wiring. The electric appliances such as metal halide lamp, high pressure sodium vapor lamp, electromagnetic induction energy saving lamp, ballast and trigger can be mounted inside. It can satisfy the related requirements of illumination in petroleum, petrochemical, medical, military, food and power supply industries.

- The degree of protection is up to IP 66.
- The bulbs of metal halide lamp and high pressure sodium vapor lamp have the function of shock protection. It is convenient to change the bulb only by operating from the side.
- There is a scale panel on the mounting bracket.
- It is convenient to be mounted and maintained.

**主要数据 Main technical data:**

防腐标志: WF1	Corrosion-proof mark: WF1
防护等级: IP66	Degree of protection: Ip66
额定电压: 220V AC 50/60Hz	Rated voltage: 220V AC 50/60Hz
220V AC, 230V AC, 240V AC, 50Hz, 60Hz	220V AC, 230V AC, 240V AC, 50Hz, 60Hz
使用环境温度: -40℃ < Ta < 50℃	Ambient temperature: -40℃ < Ta < 50℃
接线端子: L1, N 笼式端子 2-2.5mm <sup>2</sup> , PE 端子 2 × 10mm <sup>2</sup>	Terminal: L1, N cage type terminal 2-2.5mm <sup>2</sup> , PE terminal: 2 × 10mm <sup>2</sup>
电缆入口: (标配) 塑制 1 × M25 × 1.5, 电缆外径: Φ8-17mm	Cable entry: (Standard configuration) Moulded plastic 1 × M25 × 1.5, Outside diameter: Φ8-17mm
塑制 1 × M25 × 1.5 空塞堵头	Moulded plastic 1 × M25 × 1.5 stopping plug





**订购规格 Order specifications:**

图样 Illustration	光源代号 Code of light source	灯座代号 Lampholder code	功率 Power	重量 Weight	订购号 Order No.
	电磁感应节能灯-QL Electromagnetic induction energy-saving lamp-QL		85W	15.2kg	<b>M0878-QL85W57-B</b>
	金属卤化物灯-J Metal halide lamp-J	E40	250W	17.5kg	<b>M0878-J250W25-B</b>
		E40	400W	19.2kg	<b>M0878-J400W25-B</b>
	高压钠灯-N High pressure sodium vapor lamp-N	E40	250W	17.5kg	<b>M0878-N250W25-B</b>
		E40	400W	19.2kg	<b>M0878-N400W25-B</b>
	额定电压 Rated voltage ← 2 — 220V AC 3 — 230V AC 4 — 240V AC 5 — 220 ~ 240V AC 额定频率 Rated frequency ← 5 — 50Hz 6 — 60Hz 7 — 50/60Hz 电缆引入装置编码 Code of cable gland ←				




**电缆引入装置编码 Code of cable gland**

编码 Code	规格 Specification	电缆直径 Cable diameter
B	塑制 1 个 M25 × 1.5 电缆密封套, 塑制 1 个 M25 × 1.5 空塞堵头 One moulded plastic M25 × 1.5 cable gland, one moulded plastic M25 × 1.5 stopping plug	Φ8-17mm
C	铜制 1 个 CZ0221/M25 × 1.5 金属电缆密封套, 塑制 1 个 M25 × 1.5 空塞堵头 One brass CZ0221/M25 × 1.5 metal cable gland, one moulded plastic M25 × 1.5 stopping plug	Φ8-17mm
D	塑制 2 个 M25 × 1.5 电缆密封套 Two moulded plastic M25 × 1.5 cable glands	Φ8-17mm
E	铜制 2 个 CZ0221/M25 × 1.5 金属电缆密封套 Two brass CZ0221/M25 × 1.5 metal cable glands	Φ8-17mm
F	铜制 1 个 CZ0227/M25 × 1.5-G <sup>3/4</sup> 增安型金属电缆密封套, 塑制 1 个 M25 × 1.5 空塞堵头 One brass CZ0227/M25 × 1.5-G <sup>3/4</sup> increasd safety metal cable gland, one moulded plastic M25 × 1.5 stopping plug	Φ11-15mm
G	铜制 2 个 CZ0227/M25 × 1.5-G <sup>3/4</sup> 增安型金属电缆密封套 Two brass CZ0227/M25 × 1.5-G <sup>3/4</sup> increasd safety metal cable glands	Φ11-15mm
H	铜制 1 个 CZ0226/M25 × 1.5-(G02) 增安型金属电缆密封套(填料函), 塑制 1 个 M25 × 1.5 空塞堵头 One brass CZ0226/M25 × 1.5-(G02) increasd safety metal cable gland (stopping boxes), one moulded plastic M25 × 1.5 stopping plug	Φ11.5-16mm
I	铜制 2 个 CZ0226/M25 × 1.5-(G02) 增安型金属电缆密封套(填料函) Two brass CZ0226/M25 × 1.5-G02 increasd safety metal cable glands (stopping boxes)	Φ11.5-16mm


**● 光源备件 Spare parts of light source:**

图样 Illustration	功率 Power	灯座 Lampholder	光通量 Luminous flux	单位 Unit	订购号 Order No.
金属卤化物灯泡-J Metal halide lamp bulb-J 	250W	E40	20500lm	只 Piece	<b>HQI-T250/D</b>
	400W	E40	32000lm	只 Piece	<b>HQI-BT400/D</b>
高压钠灯灯泡-N High pressure sodium vapor lamp bulb-N 	250W	E40	27000lm	只 Piece	<b>NAV - T 250</b>
	400W	E40	48000lm	只 Piece	<b>NAV - T 400</b>
电磁感应节能灯泡体 Electromagnetic induction energy-saving lamp bulb   高频发生器 High frequency generator 	85W		5600lm	只 Piece	<b>WJ85P</b>
	85W		/	只 Piece	<b>HFG-85AC</b>

**● 安装附件 Mounting accessories**

图样 Illustration	描述 Descriptions	单位 Unit	订购号 Order No.
吊链式附件(500mm) Chain type accessories 	M8 吊环螺钉安装，材料为优质钢表面镀锌处理 For M8 lifting eye bolt, the material is high quality steel with galvanization on surface	套 Set	<b>D623</b>
立杆支架 Vertical bracket 	  注：可根据要求提供立杆长度和安装方式 Note:The length of the vertical pole and mounting way can be provided as per request.	只 Piece	<b>D8723/1 + □m</b>  立杆长度 (不配不注) The length of vertical pole (NO matching not noted) 3 - 10m ←

● 外形及安装尺寸 Outline and installation dimensions:



● 配光曲线 Luminous intensity distribution curve: — C0°/180°  
— C90°/270°  
光强单位 luminous intensity unit: cd/1000 Lm

