

主要数据 Main technical data:

认证 Certification | 防爆标志 Ex mark | 符合标准 Meet the standard

| | | |
|------------------------|---|----------------|
| China (PCEC Ex) | Ex de II C T5/T6 Gb (壁式插座、插头、耦式插座 Wall type socket, plug, coupler type socket) Ex de II C Gb (面板式插座 Panel type socket) | GB3836 GB12476 |
| IECEX | Ex de II C T5/T6 Gb Ex tD A21 T 95°C/80°C Ta < 55°C/45°C (壁式插座、插头、耦式插座 Wall type socket, plug, coupler type socket) Ex de II C Gb Ex tD A21 (面板式插座 Panel type socket) | IEC60079 |
| ATEX | ⊕ II 2GD Ex de II C T5/T6 Gb Ex tD A21 T 95°C/80°C Ta < 55°C/45°C (壁式插座、插头、耦式插座 Wall type socket, plug, coupler type socket) ⊕ II 2GD Ex de II C Gb Ex tD A21 (面板式插座 Panel type socket) | EN60079 |

适用范围: 用于 1 区和 2 区, 用于 21 区和 22 区

 使用环境温度: $-40^{\circ}\text{C} \leq \text{Ta} < 55^{\circ}\text{C}$

防护等级: IP66

Intended use: Can be used in zone 1 and zone 2

Can be used in zone 21 and zone 22

 Ambient temperature use: $-40^{\circ}\text{C} \leq \text{Ta} < 55^{\circ}\text{C}$

Degree of protection: IP66