


主要数据 Main technical data:

认证 Certification | 防爆标志 Ex mark | 符合标准 Meet the standard

China (PCEC Ex)	Ex nA II C T4 Gc DIP A21 Ta, T6 (产品不装熔断器不装开关 Product without fuse or switch fitted)	GB3836	GB12476
China (PCEC Ex)	Ex dmbnA II C T4 Gc DIP A21 Ta, T6 (产品装熔断器装开关 Product with fuse and switch fitted)	GB3836	GB12476
IECEX	Ex nA II C T4 Gc Ex t III C T80°C Db (产品不装熔断器不装开关 Product without fuse or switch fitted)	IEC60079	
IECEX	Ex dmbnA II C T4 Gc Ex t III C T80°C Db (产品装熔断器装开关 Product with fuse and switch fitted)	IEC60079	
ATEX	Ⓜ II 3G Ex nA II C T4 Gc II 2D Ex t III C T80°C Db (产品不装熔断器不装开关 Product without fuse or switch fitted)	EN60079	
ATEX	Ⓜ II 3G Ex dmbnA II C T4 Gc II 2D Ex t III C T80°C Db (产品装熔断器装开关 Product with fuse and switch fitted)	EN60079	

适用范围: 用于 2 区, 用于 21 区和 22 区

 使用环境温度: $-25^{\circ}\text{C} \leq \text{Ta} \leq 50^{\circ}\text{C}$

防护等级: IP66

额定电压: 100-240V AC 50-60Hz

功率: 最大 25W

色温: 6500K

 接线端子: L、N、PE, 每个端子 $2 \times 1.5-10\text{mm}^2$

 电缆入口: 塑制 $1 \times \text{M}25 \times 1.5$, 电缆外径: $\Phi 8-17\text{mm}$

 塑制 $2 \times \text{M}25 \times 1.5$ 空塞堵头

Intended use: Can be used in zone 2

Can be used in zone 21 and zone 22

 Ambient temperature: $-25^{\circ}\text{C} \leq \text{Ta} \leq 50^{\circ}\text{C}$

Degree of protection: IP66

Rated voltage: 100-240V AC 50-60Hz

Power: Max 25W

Color temperature: 6500K

Energy efficiency index EEI=A2

 Terminals: L、N、PE, Each terminal $2 \times 1.5-10\text{mm}^2$

 Cable entry: Moulded plastic $1 \times \text{M}25 \times 1.5$ cable gland,

 Outside diameter of cable: $\Phi 8-17\text{mm}$

 Moulded plastic $2 \times \text{M}25 \times 1.5$ stopping plugs

订购规格 Order specifications:

图样 Illustration	灯座代号 Lampholder code	灯管 Lamp tube	功率 Power	电流 Current	重量 Weight	订购号 Order No.
	G13 双脚灯座 G13 Two pin lampholder	T8 型 T8 Type	2 × 10W	max 0.2A	5.0kg	CZ0875 / LED2 × 10W □□T-B+□
			2 × 19W	max 0.38A	7.9kg	CZ0876 / LED2 × 19W □□T-B+□

K: 配 CZ0207 防爆行程开关 (不配不注)

K: Equipped with CZ0207 explosion-proof distance switch (no matching, not noted)

F: 配 CZ0804 防爆熔断器 (不配不注)

F: equipped with CZ0804 explosion-proof fuse module (no matching, not noted)

“PLILIPS 飞利浦” LED 灯管

“PLILIPS” LED tubes

电缆引入装置编码 Code of cable gland

安装附件订购号 (不配不注) 见 129 页

Order No. of mounting accessories (No matching not noted), see page 129

电缆引入装置编码 Code of cable gland

编码 Code	规格 Specifications	电缆直径 Cable diameter
B	塑制 1 个 $\text{M}25 \times 1.5$ 电缆密封套, 塑制 2 个 $\text{M}25 \times 1.5$ 空塞堵头 One moulded plastic $\text{M}25 \times 1.5$ cable gland, two moulded plastic $\text{M}25 \times 1.5$ stopping plugs	$\Phi 8-17\text{mm}$
C	铜制 1 个 CZ0221/ $\text{M}25 \times 1.5$ 金属电缆密封套, 塑制 2 个 $\text{M}25 \times 1.5$ 空塞堵头 One brass CZ0221/ $\text{M}25 \times 1.5$ metal cable gland, two moulded plastic $\text{M}25 \times 1.5$ stopping plugs	$\Phi 8-17\text{mm}$
D	塑制 2 个 $\text{M}25 \times 1.5$ 电缆密封套, 塑制 1 个 $\text{M}25 \times 1.5$ 空塞堵头 Two moulded plastic $\text{M}25 \times 1.5$ cable glands, one moulded plastic $\text{M}25 \times 1.5$ stopping plug	$\Phi 8-17\text{mm}$
E	铜制 2 个 CZ0221/ $\text{M}25 \times 1.5$ 金属电缆密封套, 塑制 1 个 $\text{M}25 \times 1.5$ 空塞堵头 Two brass CZ0221/ $\text{M}25 \times 1.5$ metal cable glands, one moulded plastic $\text{M}25 \times 1.5$ stopping plug	$\Phi 8-17\text{mm}$
F	铜制 1 个 CZ0227/ $\text{M}25 \times 1.5 \text{ G}^{3/4}$ 增安型金属电缆密封套, 塑制 2 个 $\text{M}25 \times 1.5$ 空塞堵头 One brass CZ0227/ $\text{M}25 \times 1.5 \text{ G}^{3/4}$ increased safety metal cable gland, two moulded plastic $\text{M}25 \times 1.5$ stopping plugs	$\Phi 11-15\text{mm}$
G	铜制 2 个 CZ0227/ $\text{M}25 \times 1.5 \text{ G}^{3/4}$ 增安型金属电缆密封套, 塑制 1 个 $\text{M}25 \times 1.5$ 空塞堵头 Two brass CZ0227/ $\text{M}25 \times 1.5 \text{ G}^{3/4}$ increased safety metal cable glands, one moulded plastic $\text{M}25 \times 1.5$ stopping plug	$\Phi 11-15\text{mm}$
H	铜制 1 个 CZ0226/ $\text{M}25 \times 1.5 \text{ G}^{02}$ 增安型金属电缆密封套(填料函), 塑制 2 个 $\text{M}25 \times 1.5$ 空塞堵头 One brass CZ0226/ $\text{M}25 \times 1.5 \text{ G}^{02}$ increased safety metal cable gland (stopping boxes), two moulded plastic $\text{M}25 \times 1.5$ stopping plugs	$\Phi 11.5-16\text{mm}$
I	铜制 2 个 CZ0226/ $\text{M}25 \times 1.5 \text{ G}^{02}$ 增安型金属电缆密封套(填料函), 塑制 1 个 $\text{M}25 \times 1.5$ 空塞堵头 Two brass CZ0226/ $\text{M}25 \times 1.5 \text{ G}^{02}$ increased safety metal cable glands (stopping boxes), one moulded plastic $\text{M}25 \times 1.5$ stopping plug	$\Phi 11.5-16\text{mm}$